



SAFETY DATA SHEET

SECTION 1. Identification

Trade Name: No. 394 SmartPlate® Prep
Chemical names, common names: Water base abrasive solution

Manufacturer's Name: HURST CHEMICAL COMPANY
Address: 2360 Eastman Avenue # 108, Oxnard, CA 93030
Product Information, Call: (800) 723-2004
FOR EMERGENCY, CALL CHEMTREC, 24 HOUR: (800) 424-9300
DOT CLASSIFICATION: (Not regulated)

Recommended Use: Removes scattered toner particles; contains wetting agents.
Restrictions on Use: Not intended for any other use other than the recommended use of this product. Persons handling and/or using this product should be trained regarding handling and use.

SECTION 2. Hazard(s) Identification

HMIS Health Hazard = 1
HAZARD Flammability = 1
CLASS Reactivity = 0

0 = Least	3 = High
1 = Slight	4 = Extreme
2 = Moderate	

Other: Safety glasses, nitrile gloves.
Flash Point °F: > 200
Flammable class: IIIB

Signal Word: Danger

Hazard Statement(s):

Unusual fire and explosion hazard: Not known.
The product is not flammable. However vapors exposed to heat or open flame may separate and become flammable. Then use dry chemical or foam to extinguish.
Ingestion of excessive amount may cause irritation of digestive tract, signs of nervous system depression, visual disturbances, kidney damage, convulsions, & coma. Maybe toxic if swallowed.
Chronic: Kidney damage & visual disturbances. Harmful in contact with skin

Pictograms or hazard symbols:



Precautionary statement(s):

Wash affected areas thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Keep away from open flames/hot surfaces.

Mixture composition and information on ingredients are described in Section 3.

SECTION 3. Composition/ Information on Ingredients

<u>Chemical Names</u>	<u>CAS Number</u>	<u>Weight % Range</u>
2-Butoxyethanol	111-76-2	10-20
Ethylene glycol	107-21-1	3-10
Water	7732-18-5	

SECTION 4. First-Aid Measures

SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE

Inhaled: This product has low degree of toxicity. Breathing high concentrations of vapors or mists may cause irritation of nose, throat and signs of nervous system depression.
Contact with skin or eyes: This material may cause skin and eye irritation. Direct contact may cause redness, tearing and burning of the eyes and redness, drying and cracking of skin.

Absorbed through skin: No data available of harmful effects through skin absorption.

Swallowed: Ingestion of excessive amount may cause irritation of digestive tract, signs of nervous system depression, visual disturbances, kidney damage, convulsions, coma.

HEALTH EFFECTS OR RISKS FROM EXPOSURE

Acute: May cause eye, skin & digestive track irritation.
Chronic: Kidney damage & visual disturbances.

EMERGENCY PROCEDURES

Eye Contact: For direct contact, hold eyelids apart and flush the affected eye (s) with clean water for 15 minutes, if irritation or redness develops, seek medical attention.

Skin Contact: Remove contaminated clothing, cleanse affected area (s) thoroughly by washing with mild soap & water. If irritation or redness develops, seek medical attention.

Inhaled: Move victim away from source of exposure and into fresh air. If symptoms appear seek medical attention.

Swallowed: Seek immediate medical attention, do not induce vomiting.

COMMENTS: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC or OSHA. Ethylene glycol in this product is a probable hazard to the fetus based on tests with laboratory animals. 2-Butoxyethanol has caused blood disorders resulting in liver, kidney and spleen disorders in long term studies in laboratory animals. Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain & nervous system damage, (Sometimes referred to as solvent or painter's syndrome). Intentional misuse by deliberately concentrating & inhaling this

product may be harmful or fatal.

SECTION 5. Fire-fighting Measures

Flash Point °F: > 200

Fire extinguishing materials: Do not use water spray, carbon dioxide, foam or dry chemical. See special firefighting procedures below.

Special firefighting procedures: The product is not flammable. However vapors exposed to heat or open flame may separate and become flammable. Then use dry chemical or foam to extinguish.

Unusual fire and explosion hazard: Not known.

SECTION 6. Accidental Release Measures

Spill response procedures: For small spills, do not flush with water, use absorbent pads. Keep out of drains, sewers or waterways. Use sand or other inert material to dam and contain spill.

SECTION 7: Handling and Storage

Keep containers tightly closed. Keep containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 8. Exposure Controls/ Personal Protection

<u>Chemical Names</u>	<u>CAS Number</u>	<u>Exposure Limits in Air</u>	
		<u>ACGIH (TWA)</u>	<u>OSHA (PEL)</u>
2-Butoxyethanol	111-76-2	25 ppm	25 ppm
Ethylene glycol	107-21-1	50 ppm Ceil.	50 ppm Ceil
Water	7732-18-5	None	None

Ventilation and engineering controls: Normal shop ventilation is adequate.

Respiratory Protection: In working atmosphere where TLV or PEL levels are exceeded, use NIOSH approved chemical cartridge respirator.

Eye Protection: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

Gloves: The use of nitrile gloves impermeable to the specific material handled is advised.

Other clothing and equipment: It is suggested that a source of clean water be available in work area for flushing eyes & skin. Impervious clothing should be worn as needed.

SECTION 9. Physical and Chemical Properties

- Appearance (physical state, color, etc.): White thick liquid
- Upper/lower flammability or explosive limits: in air, volume %: lower: N/A -upper: N/A
- Vapor Density (air = 1): <1
- Odor: Information may not be relevant or is not available.
- Vapor pressure: Information may not be relevant or is not available.
- Odor threshold: Information may not be relevant or is not available.
- Vapor density: Density lb/gal: 2.92
- pH: Information may not be relevant or is not available.
- Relative density: Information may not be relevant or is not available.
- Melting point/freezing point: Information may not be relevant or is not available.
- Solubility(ies): in water: 100%
- Initial boiling point and boiling range: Boiling Range °F: 212
- VOC Composite Partial Pressure, mm Hg at 20°C: < 1
- Volatile Organic Content (VOC,EPA Method 24): 191gm/l or 1.59 lb/gal
- Flash point: °F: > 200
- Evaporation rate: (Bu Ac = 1): <1
- Flammability (solid, gas): Flammable class: IIIB
- Partition coefficient: n-octanol/water: Information may not be relevant or is not available.
- Auto-ignition temperature: Information may not be relevant or is not available.
- Decomposition temperature: Information may not be relevant or is not available.
- Viscosity: Information may not be relevant or is not available.
- Specific Gravity: 1.18

SECTION 10. Stability and Reactivity

Reactivity

Fire and Explosion: CLASS / Reactivity=0, 0=Least

Chemical stability

Stability: Stable under ordinary use & storage.

Other

Incompatibility (materials to avoid): Incompatible with strong oxidizing agents, anhydride, isocyanate, acetaldehyde, chlorine, ethylene oxide, hydrogen peroxide, aluminum and organometallic contaminants.

Hazardous Decomposition products (including combustion products): Carbon monoxide/ or carbon dioxide, oxides of nitrogen.

Hazardous polymerization: Will not occur.

SECTION 11. Toxicological Information

Routes of exposure (inhalation, ingestion, skin and eye contact are discussed in Section 4. Description of the delayed, immediate, or chronic effects from short- and long-term exposure is discussed in Section 4. Description of the symptoms is discussed in Section 4.

No additional data is available.

SECTION 12. Ecological Information

Keep out of sewers, drainage areas, and waterways. Consult appropriate local, county, state, and federal agencies regarding ecological issues. Follow appropriate spill response measures as outlined in Section 6.

SECTION 13 Disposal Considerations

Preparing wastes for disposal: Dispose of product in accordance with local ordinance

SECTION 14. Transport Information

Transport this product in accordance with local, county, state, and federal regulations.

SECTION 15. Regulatory Information

Section IIA -This product contains the following chemicals subject to reporting requirements of 40 CFR 372 and Environment Canada's NDSL: None

This product contains the following chemicals subject to reporting requirements of SARA 313: Ethylene glycol

This product contains the following chemicals subject to reporting requirements of TSCA: 2-Butoxyethanol, Ethylene glycol

This product contains the following chemicals subject to Environment Canada's DSL: All

SECTION 16. Other Information

Date Prepared: March 1998

Date Reviewed: May 2015

Hurst Chemical Company furnishes Safety Data Sheets based upon information from raw material suppliers. This information is provided in compliance with Federal Regulation 29CFR 1910. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.